15

20

CLAIMS

- Process for the preparation of a thermoplastic elastomer by melt mixing.
 - a. a partially vulcanized rubber concentrate
- 5 b. a thermoplastic polymer and/or additives
 - c. optionally oil and
 - d. a curing agent.
 - Process according to claim 1 characterized in that the melt mixing is carried out in a twin-screw extruder.
- Process according to claim 1 characterized in that the melt mixing is carried out in a single screw extruder.
 - Process according to any one of the claims 1-3 characterized in that the partially vulcanized rubber concentrate (a) is prepared by melt mixing:
 - e. at least one elastomer and optionally oil
 - f. at least one thermoplastic polymer
 - a curing agent.
 - Process according to claim 4 characterized in that the partially vulcanized rubber concentrate is prepared by melt mixing
 - e. 30 to 95 parts by weight of the elastomer(s) and 0-70 parts by weight of oil
 - f. 5 to 50 parts by weight of the thermoplastic polymer(s)
 - g. 0,1-10 parts by weight of the curing agent whereby the sum of the parts by weight of the elastomer(s), the thermoplastic polymer(s), curing agent and oil is 100.
- Process according to any one of claims 4-5 characterized in that the elastomer is EPDM or EPM.
 - Process according to claim 1-6 characterized in that the thermoplastic polymer is chosen from thermoplastic polyolefin homo- and copolymers, reactor TPO, polyamides, polycarbonate, polyesters, polysulfones, polylactones,
- 30 polyacetals, acrylonitrile-butadiene-styrene (ABS) resins, polyphenylene oxide (PPO), polyphenylene sulfide (PPS), styrene-acrylonitrile (SAN) resins, polyimides, styrene maleic anhydride (SMA) and aromatic polyketones.
 - Process according to claim 7 characterized in that the thermoplastic polymer is a thermoplastic polyolefin homo- and copolymer.
- 35 9. Process according to claim 8 characterized in that the thermoplastic polymer

is a polypropylene homopolymer.

- Process according to any one of claims 1-9 characterized in that the elastomer in the partially vulcanized rubber concentrate has a gel content higher than 50%.
- 5 11. Process according to any one of claims 1-10 characterized in that the elastomer in the partially vulcanized rubber concentrate has a gel content higher than 70%.
 - Process for the preparation of a thermoplastic elastomer according to claims
 1-11 by melt mixing:
 - a. 10-90 parts by weight of the partially vulcanized rubber concentrate
 - 90-10 parts by weight of a the thermoplastic polymer and/or additives
 - c. 0-30 parts by weight of oil
 - d. 0,1-10 parts by weight of the curing agent
- 15 whereby the sum of the parts by weight of the partially vulcanized rubber concentrate, the thermoplastic polymer and/or additives, the oil and the curing agent is 100.
 - Process according to any one of claims 1-12 characterized in that the curing agent is chosen from phenol resins, siloxanes or peroxides.

20

13.

10